

ECO-SUPER-HEIZOEL

Revision date: 14.06.2024

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

ECO-SUPER-HEIZOEL

UFI: AWCA-3WHH-EW0G-9043

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Liquid fuels.

1.3. Details of the supplier of the safety data sheet

Company name:	Wilhelm Hoyer B.V. & Co. KG	
Street:	Rudolf-Diesel-Straße 1	
Place:	D-27374 Visselhövede	
Telephone:	+49 (4262) 797	Telefax: +49 (4262) 4040
E-mail:	sicherheitsdatenblatt@hoyer.de	
Contact person:	Technical Service	Telephone: +49 (4262) 79 9603
Responsible Department:	Technical Service	

1.4. Emergency telephone number: +49 (551) 19240
Giftinformationszentrum - Nord

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226
Carc. 2; H351
Acute Tox. 4; H332
Skin Irrit. 2; H315
STOT RE 2; H373
Asp. Tox. 1; H304
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Fuels, diesel, Gasoil - unspecified

Signal word: Danger**Pictograms:****Hazard statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

ECO-SUPER-HEIZOEL

Revision date: 14.06.2024

Page 2 of 11

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P331	Do NOT induce vomiting.
P501	Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Contains: Hydrocarbons (C9 - C28), Additive, Colouring agent, dyestuff.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
68334-30-5	Fuels, diesel, Gasoil - unspecified			100 %
	269-822-7	649-224-00-6	01-2119484664-27	
	Flam. Liq. 3, Carc. 2, Acute Tox. 4, Skin Irrit. 2, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H226 H351 H332 H315 H373 H304 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68334-30-5	269-822-7	Fuels, diesel, Gasoil - unspecified	100 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 4,1 mg/l (dusts or mists); dermal: LD50 = > 4300 mg/kg; oral: LD50 = 17900 mg/kg		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!

Move victim out of danger zone.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If victim is at risk of losing consciousness, position and transport on their side.

In case of irregular breathing or respiratory arrest provide artificial respiration. Where appropriate artificial ventilation. Call a physician immediately.

After contact with skin

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of

**ECO-SUPER-HEIZOEL**

Revision date: 14.06.2024

Page 3 of 11

water and soap. After cleaning apply high-fat content skin care cream.

In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Provide fresh air. Rinse mouth immediately and drink plenty of water.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Headache, Dizziness, Dizziness, Inebriation, Dyspnoea, Impaired consciousness, Vomiting.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Harmful if inhaled.

May cause damage to organs through prolonged or repeated exposure.

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Warning after ingestion: Caution if victim vomits: Risk of aspiration! Subsequent observance for pneumonia and lung oedema.

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder, Foam, Carbon dioxide (CO₂), Water fog.

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove persons to safety. Do not breathe vapour/aerosol. Provide adequate ventilation.

In case of leakage, eliminate all ignition sources. Use non-sparking tools.

Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

**ECO-SUPER-HEIZOEL**

Revision date: 14.06.2024

Page 4 of 11

Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up**Other information**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Remove from the water surface (e.g. skimming, sucking).

High slip hazard because of leaking or spilled product.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Personal protection equipment: refer to chapter 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not breathe vapour/aerosol. Provide adequate ventilation as well as local exhaust at critical locations.

Avoid contact with skin and eyes. Take off immediately all contaminated clothing. For industrial purposes only.

Advice on protection against fire and explosion

Flammable liquid and vapour.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Vapours are heavier than air and will spread at floor level. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

Advice on general occupational hygiene

Do not eat, drink, smoke or sneeze at the workplace. Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes. Take off contaminated clothing and wash it before reuse. Protect skin by using skin protective cream. Wash hands before breaks and after work. After cleaning apply high-fat content skin care cream. Do not put any product-impregnated cleaning rags into your trouser pockets. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Further information on handling

Ground and bond container and receiving equipment.

Use non-sparking tools.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store in a place accessible by authorized persons only.

Only use containers specifically approved for the substance/product.

Keep container tightly closed in a cool, well-ventilated place.

Always close containers tightly after the removal of product.

Recommended storage temperature: 5 - 30 °C.

Hints on joint storage

Do not store together with: Oxidising agent,

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Protect against: Heat, Light, Frost, moisture.

Protect from direct sunlight.

7.3. Specific end use(s)

Liquid fuels.

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection



ECO-SUPER-HEIZOEL

Revision date: 14.06.2024

Page 5 of 11

8.1. Control parameters**DNEL/DMEL values**

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
68334-30-5	Fuels, diesel, Gasoil - unspecified			
Worker DNEL, long-term		dermal	systemic	2,9 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	68 mg/m ³
Worker DNEL, acute		inhalation	systemic	4300 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,3 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	20 mg/m ³
Consumer DNEL, acute		inhalation	systemic	2600 mg/m ³

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses. (EN 166)

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN 420, EN ISO 374.

Suitable material: NBR (Nitrile rubber), FKM (fluoro rubber).

Unsuitable material: Textile material. Required properties: liquid-tight.
penetration time (maximum wearing period): > 480 min.

Thickness of glove material: 0,4 mm

Before using check leak tightness / impermeability.

Skin protection

Handling larger quantities: Wear suitable protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist generation.

Suitable respiratory protective equipment: A gas filtering equipment (EN 141). AP Combination filter device (DIN EN 141)..

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	red
Odour:	characteristic

Test method**Changes in the physical state**

Melting point/freezing point:

No data available.

Boiling point or initial boiling point and
boiling range:

approx. 150 - 380 °C EN ISO 3405

**ECO-SUPER-HEIZOEL**

Revision date: 14.06.2024

Page 6 of 11

Flash point: > 55 °C ASTM D 93

Explosive properties

In use may form flammable/explosive vapour-air mixture.

Lower explosion limits: approx. 0,5 vol. %

Upper explosion limits: approx. 6,5 vol. %

Auto-ignition temperature: > 220 °C ASTM E 659-78

pH-Value: not applicable

Viscosity / kinematic:
(at 40 °C) < 7 mm²/s DIN 51562

Partition coefficient n-octanol/water: Log KOW > 3

Density (at 15 °C): approx. 0,820 - 0,845 g/cm³

Relative vapour density: > 5

9.2. Other information**Information with regard to physical hazard classes**

Oxidizing properties

No data available.

Other safety characteristics**Further Information**

none

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable liquid and vapour.

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

In use may form flammable/explosive vapour-air mixture.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong acid, Strong alkali, Oxidising agent, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide.**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 11,00 mg/l; ATE (inhalation dust/mist) 4,100 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**ECO-SUPER-HEIZOEL**

Revision date: 14.06.2024

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68334-30-5	Fuels, diesel, Gasoil - unspecified				
	oral	LD50 17900 mg/kg	Rat		OECD 401
	dermal	LD50 > 4300 mg/kg	Rabbit		
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) dust/mist	LC50 4,1 mg/l	Rat		OECD 403

Irritation and corrosivity

Irritant effect on the skin: Causes skin irritation.

Irritant effect on the eye: slightly irritant but not relevant for classification.

Sensitising effects

Respiratory or skin sensitisation: not sensitising. No known symptoms to date.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Fuels, diesel, Gasoil - unspecified)

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Fuels, diesel, Gasoil - unspecified)

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68334-30-5	Fuels, diesel, Gasoil - unspecified					
	Acute fish toxicity	LC50 21 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		OECD 203
	Acute algae toxicity	ErC50 22 mg/l	72 h	Pseudokirchneriella subcapitata		OECD 201
	Acute crustacea toxicity	EC50 68 mg/l	48 h	Daphnia magna (Big water flea)		OECD 202
	Fish toxicity	NOEC 0,083 mg/l	14 d			QSAR

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria).

ECO-SUPER-HEIZOEL

Revision date: 14.06.2024

Page 8 of 11

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
68334-30-5	Fuels, diesel, Gasoil - unspecified			
	OECD 301F	60%	28	
	Easily biodegradable (concerning to the criteria of the OECD)			

12.3. Bioaccumulative potential

Log KOW > 3.

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment cannot be ruled out.

12.4. Mobility in soil

Physical state at 20 °C and 101.3 kPa: liquid.

If product enters soil, it will be mobile and may contaminate groundwater

Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Discharge into the environment must be avoided.

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

Dispose of waste according to applicable legislation.

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

The waste key according to the European Waste Catalogue (EWC number) refers to the real wastes origin and therefore is not product- but use-oriented.

Consult the local waste disposal expert about waste disposal.

List of Wastes Code - residues/unused products

130701 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); wastes of liquid fuels; fuel oil and diesel; hazardous waste

List of Wastes Code - used product

130701 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); wastes of liquid fuels; fuel oil and diesel; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste



ECO-SUPER-HEIZOEL

Revision date: 14.06.2024

Page 9 of 11

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1202
14.2. UN proper shipping name: HEATING OIL, LIGHT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 640L ADR664
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1202
14.2. UN proper shipping name: HEATING OIL, LIGHT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 640L
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1202
14.2. UN proper shipping name: HEATING OIL, LIGHT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: -
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1202

ECO-SUPER-HEIZOEL

Revision date: 14.06.2024

Page 10 of 11

14.2. UN proper shipping name: HEATING OIL, LIGHT**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1

IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: HEATING OIL, LIGHT

14.6. Special precautions for user

Handling (Transport information): See protective measures under point 7 and 8.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III):	34 Petroleum products and alternative fuels (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams) (-)
---	---

Additional information

Safety Data Sheet according to Regulation (EC) No 1907/2006 (amended by Regulation (EU) No 2020/878)

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	---

Water hazard class (D):	2 - obviously hazardous to water
-------------------------	----------------------------------

Additional information

Restricted to professional users.

The receiver of our product is singularly responsible for adhering to existing laws and regulations. Observe in addition any national regulations!

15.2. Chemical safety assessment

For this mixture a chemical safety assessment has been carried out.

SECTION 16: Other information



ECO-SUPER-HEIZOEL

Revision date: 14.06.2024

Page 11 of 11

Changes

This data sheet contains changes from the previous version in section(s): 2,11,12,15,16.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Carc. 2; H351	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
STOT RE 2; H373	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)