

**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>**

Revision date: 03.02.2025

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**
**1.1. Product identifier**
MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>

Substance name: Fuel oil, No 2, Gasoil - unspecified  
 REACH Registration Number: 01-2119475501-42-0009  
 CAS No: 68476-30-2  
 EC No: 270-671-4  
 UFI: GRUX-P2RN-0X0S-16A2

**1.2. Relevant identified uses of the substance or mixture and uses advised against**
**Use of the substance/mixture**

Product Categories [PC]: PC 13 Fuels.

**1.3. Details of the supplier of the safety data sheet**

Company name: Wilhelm Hoyer B.V. & Co. KG  
 Street: Rudolf-Diesel-Straße 1  
 Place: D-27374 Visselhövede  
 Telephone: +49 (4262) 797  
 E-mail: sicherheitsdatenblatt@hoyer-energie.de  
 Contact person: Technical Service  
 Responsible Department: Technical Service

Telefax: +49 (4262) 4040

Telephone: +49 (4262) 79 9603

**1.4. Emergency telephone**
**number:** +49 (551) 19240  
 Giftinformationszentrum - Nord

**SECTION 2: Hazards identification**
**2.1. Classification of the substance or mixture**
**Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226  
 Carc. 2; H351  
 Acute Tox. 4; H332  
 Skin Irrit. 2; H315  
 STOT RE 2; H373  
 Asp. Tox. 1; H304  
 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**
**Regulation (EC) No 1272/2008**
**Signal word:** Danger

**Pictograms:**

**Hazard statements**

H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H332 Harmful if inhaled.  
 H351 Suspected of causing cancer.


**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>**

Revision date: 03.02.2025

Page 2 of 10

H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P264 Wash hands thoroughly after handling.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P331 Do NOT induce vomiting.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P370+P378 In case of fire: Use Water mist, Foam, Dry extinguishing powder, Carbon dioxide (CO<sub>2</sub>) to extinguish.  
 P391 Collect spillage.  
 P501 Dispose of contents/container to hazardous or special waste collection point.

**2.3. Other hazards**

This substance does not meet the criteria for classification as PBT or vPvB.

**SECTION 3: Composition/information on ingredients**
**3.1. Substances****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
68476-30-2	Fuel oil, No 2, Gasoil - unspecified			100 %
	270-671-4		01-2119475501-42-0009	
	Flam. Liq. 3, Carc. 2, Acute Tox. 4, Skin Irrit. 2, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H226 H351 H332 H315 H373 H304 H411			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68476-30-2	270-671-4	Fuel oil, No 2, Gasoil - unspecified	100 %
	inhalation: LC50 = 4100 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 2000 mg/kg		

**SECTION 4: First aid measures**
**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!

Move victim out of danger zone.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After inhalation**

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>**

Revision date: 03.02.2025

Page 3 of 10

breathing. If victim is at risk of losing consciousness, position and transport on their side.  
In case of irregular breathing or respiratory arrest provide artificial respiration. Where appropriate artificial ventilation. Call a physician immediately.

**After contact with skin**

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. After cleaning apply high-fat content skin care cream.  
In case of skin irritation, seek medical treatment.

**After contact with eyes**

Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Provide fresh air. Rinse mouth immediately and drink plenty of water.  
IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, Dizziness, Dizziness, Inebriation, Dyspnoea, Impaired consciousness, Vomiting.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Suspected of causing cancer.  
Harmful if inhaled.  
May cause damage to organs through prolonged or repeated exposure.  
In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

Warning after ingestion: Caution if victim vomits: Risk of aspiration! Subsequent observance for pneumonia and lung oedema.  
First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder, Dry extinguishing powder, Foam, Carbon dioxide (CO<sub>2</sub>), Water fog.  
Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Vapours can form explosive mixtures with air.  
In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide.

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.  
In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Move undamaged containers from immediate hazard area if it can be done safely.  
Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>**

Revision date: 03.02.2025

Page 4 of 10

**General advice**

- Remove persons to safety. Do not breathe vapour/aerosol. Provide adequate ventilation.
- In case of leakage, eliminate all ignition sources. Use non-sparking tools.
- Avoid contact with skin, eyes and clothes. Wear personal protection equipment.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.2. Environmental precautions**

- Do not allow to enter into surface water or drains.
- Do not allow to enter into soil/subsoil.

**6.3. Methods and material for containment and cleaning up****Other information**

- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Remove from the water surface (e.g. skimming, sucking).
- High slip hazard because of leaking or spilled product.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
- Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

- Personal protection equipment: refer to chapter 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

- Do not breathe vapour/aerosol. Provide adequate ventilation as well as local exhaustion at critical locations.
- Avoid contact with skin and eyes. Take off immediately all contaminated clothing. For industrial purposes only.

**Advice on protection against fire and explosion**

- Flammable liquid and vapour.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Vapours are heavier than air and will spread at floor level. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

**Advice on general occupational hygiene**

- Do not eat, drink, smoke or sneeze at the workplace.
- Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes.
- Take off contaminated clothing and wash it before reuse.
- Protect skin by using skin protective cream.
- Wash hands before breaks and after work.
- After cleaning apply high-fat content skin care cream.
- Do not put any product-impregnated cleaning rags into your trouser pockets.
- Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

**Further information on handling**

- Ground and bond container and receiving equipment.
- Use non-sparking tools.
- Take precautionary measures against static discharges.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

- Store in a place accessible by authorized persons only.
- Only use containers specifically approved for the substance/product.
- Keep container tightly closed in a cool, well-ventilated place.
- Always close containers tightly after the removal of product.
- Recommended storage temperature: 5 - 30 °C.

**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>**

Revision date: 03.02.2025

Page 5 of 10

**Hints on joint storage**

Do not store together with: Oxidising agent,  
Keep away from food, drink and animal feedingstuffs.

**Further information on storage conditions**

Protect against: Heat, Light, Frost, moisture. Protect from direct sunlight.

**7.3. Specific end use(s)**

Fuels.  
Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Additional advice on limit values**

Air limit values:  
Limit value type (country of origin): US-OSHA PEL-Value: 5 mg/m<sup>3</sup>  
Limit value type (country of origin): ACGIH STEL-Value: 10 mg/m<sup>3</sup>

**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaustion at critical locations.  
Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses. (EN 166)

**Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN 420, EN ISO 374.  
Suitable material: NBR (Nitrile rubber), FKM (fluoro rubber).  
Unsuitable material: Textile material.  
Required properties: liquid-tight.  
penetration time (maximum wearing period): > 480 min.  
Thickness of glove material: 0,4 mm  
Before using check leak tightness / impermeability.

**Skin protection**

Handling larger quantities: Wear suitable protective clothing.

**Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required.  
Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist generation.  
Suitable respiratory protective equipment: A gas filtering equipment (EN 141). AP Combination filter device (DIN EN 141)..

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	light brown
Odour:	characteristic

**Test method****Changes in the physical state**

Melting point/freezing point: No data available.


**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>**

Revision date: 03.02.2025

Page 6 of 10

Boiling point or initial boiling point and boiling range:	approx. 160 - 400 °C
Flash point:	> 55 °C ASTM D 93
<b>Explosive properties</b>	
In use may form flammable/explosive vapour-air mixture.	
Lower explosion limits:	approx. 0,6 vol. %
Upper explosion limits:	approx. 6,5 vol. %
Auto-ignition temperature:	220 °C ASTM E 659-78
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	approx. 2,0 - 4,5 mm <sup>2</sup> /s
Partition coefficient n-octanol/water:	Log KOW > 3
Vapour pressure: (at 38 °C)	550 - 650 hPa
Density (at 15 °C):	0,89 g/cm <sup>3</sup>
Relative vapour density:	> 3

**9.2. Other information**
**Information with regard to physical hazard classes**

Oxidizing properties  
No data available.

**Other safety characteristics**
**Further Information**

none

**SECTION 10: Stability and reactivity**
**10.1. Reactivity**

Flammable liquid and vapour.  
No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

In use may form flammable/explosive vapour-air mixture.

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Strong acid, Strong alkali, Oxidising agent, strong.

**10.6. Hazardous decomposition products**

Thermal decomposition can lead to the escape of irritating gases and vapours.  
In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide, Sulphur dioxide (SO<sub>2</sub>).

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**
**Toxicokinetics, metabolism and distribution**

No information available.


**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>**

Revision date: 03.02.2025

Page 7 of 10

**Acute toxicity**

Harmful if inhaled.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68476-30-2	Fuel oil, No 2, Gasoil - unspecified				
	oral	LD50 > 2000 mg/kg	Rat		OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4100 mg/l	Rat		OECD 403
	inhalation dust/mist	ATE 1,5 mg/l			

**Irritation and corrosivity**

Irritant effect on the skin: Causes skin irritation.

Irritant effect on the eye: slightly irritant but not relevant for classification.

**Sensitising effects**

Respiratory or skin sensitisation: not sensitising. No known symptoms to date.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of causing cancer. (Fuel oil, No 2, Gasoil - unspecified)

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (Fuel oil, No 2, Gasoil - unspecified)

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**11.2. Information on other hazards****Endocrine disrupting properties**

Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**
**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria).

**12.3. Bioaccumulative potential**

Log KOW &gt; 3.

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment cannot be ruled out.

**12.4. Mobility in soil**

Physical state at 20 °C and 101.3 kPa: liquid.

If product enters soil, it will be mobile and may contaminate groundwater

Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants.

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>**

Revision date: 03.02.2025

Page 8 of 10

**12.7. Other adverse effects**

No information available.

**Further information**

Discharge into the environment must be avoided.

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

Dispose of waste according to applicable legislation.

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

The waste key according to the European Waste Catalogue (EWC number) refers to the real wastes origin and therefore is not product- but use-oriented.

Consult the local waste disposal expert about waste disposal.

**List of Wastes Code - residues/unused products**

130701 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); wastes of liquid fuels; fuel oil and diesel; hazardous waste

**List of Wastes Code - used product**

130701 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); wastes of liquid fuels; fuel oil and diesel; hazardous waste

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

**SECTION 14: Transport information**
**Land transport (ADR/RID)****14.1. UN number or ID number:** UN 1202**14.2. UN proper shipping name:** GAS OIL**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Classification code: F1

Special Provisions: 640L ADR664

Limited quantity: 5 L

Excepted quantity: E1

Transport category: 3

Hazard No: 30



**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm3**

Revision date: 03.02.2025

Page 9 of 10

Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1202  
**14.2. UN proper shipping name:** GAS OIL  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Special Provisions: 640L  
 Limited quantity: 5 L  
 Excepted quantity: E1

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1202  
**14.2. UN proper shipping name:** GAS OIL  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Special Provisions: -  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1202  
**14.2. UN proper shipping name:** GAS OIL  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Special Provisions: A3  
 Limited quantity Passenger: 10 L  
 Passenger LQ: Y344  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 355  
 IATA-max. quantity - Passenger: 60 L  
 IATA-packing instructions - Cargo: 366  
 IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: GAS OIL



according to Regulation (EC) No 1907/2006

**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,89 g/cm<sup>3</sup>**

Revision date: 03.02.2025

Page 10 of 10

**14.6. Special precautions for user**

Handling (Transport information): See protective measures under point 7 and 8.

**14.7. Maritime transport in bulk according to IMO instruments**

MARPOL Anlage I.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive  
2012/18/EU (SEVESO III):34 Petroleum products and alternative fuels (c) gas oils (including diesel  
fuels, home heating oils and gas oil blending streams) (-)**Additional information**

Safety Data Sheet according to Regulation (EC) No 1907/2006 (amended by Regulation (EU) No 2020/878)

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile  
work protection guideline' (94/33/EC). Observe employment restrictions  
under the Maternity Protection Directive (92/85/EEC) for expectant or  
nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

**Additional information**

Restricted to professional users.

The receiver of our product is singularly responsible for adhering to existing laws and regulations. Observe in  
addition any national regulations!**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has been carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2,5,10,11,12,15,16.

**Relevant H and EUH statements (number and full text)**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

**Further Information**The information is based on the present level of our knowledge. It does not, however, give assurance of  
product properties and establishes no contract legal rights.