

MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³

Revision date: 17.03.2023

Product code: 2555-1

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier
MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³

UFI: KV2V-J2HN-QX0V-JTKJ

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

Product Categories [PC]: PC 13 Fuels.

1.3. Details of the supplier of the safety data sheet

Company name:	Hoyer Marine GmbH	
Street:	Palmaille 63	
Place:	D-22767 Hamburg	
Telephone:	+49 (40) 53798470	
e-mail:	sicherheitsdatenblatt@hoyer-energie.de	
Contact person:	Technical Service	Telephone: +49 (4262) 799603
Internet:	www.hoyer-energie.de	

1.4. Emergency telephone number: +356 25456508

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
Regulation (EC) No 1272/2008


Flam. Liq. 3; H226
 Carc. 2; H351
 Acute Tox. 4; H332
 Skin Irrit. 2; H315
 STOT RE 2; H373
 Asp. Tox. 1; H304
 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements
Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:


Hazard statements

H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.



according to Regulation (EC) No 1907/2006

MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³

Revision date: 17.03.2023

Product code: 2555-1

Page 2 of 10

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

This substance does not meet the criteria for classification as PBT or vPvB.

SECTION 3: Composition/information on ingredients**3.1. Substances****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
68476-30-2	Fuel oil, No 2, Gasoil - unspecified	100 %
	270-671-4	
	01-2119475501-42-0009	
	Flam. Liq. 3, Carc. 2, Acute Tox. 4, Skin Irrit. 2, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H226 H351 H332 H315 H373 H304 H411	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
68476-30-2	270-671-4	Fuel oil, No 2, Gasoil - unspecified	100 %
		inhalation: LC50 = 4100 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 2000 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!

Move victim out of danger zone.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If victim is at risk of losing consciousness, position and transport on their side.

In case of irregular breathing or respiratory arrest provide artificial respiration. Where appropriate artificial ventilation. Call a physician immediately.

After contact with skin

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. After cleaning apply high-fat content skin care cream.

In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of troubles or persistent symptoms, consult an ophthalmologist.

MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³

Revision date: 17.03.2023

Product code: 2555-1

Page 3 of 10

After ingestion

Provide fresh air. Rinse mouth immediately and drink plenty of water.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Headache, Dizziness, Dizziness, Inebriation, Dyspnoea, Impaired consciousness, Vomiting.

Suspected of causing cancer.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Harmful if inhaled.

May cause damage to organs through prolonged or repeated exposure.

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Warning after ingestion: Caution if victim vomits: Risk of aspiration! Subsequent observance for pneumonia and lung oedema.

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder, Foam, Carbon dioxide (CO₂), Water fog.

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

Additional information

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove persons to safety. Do not breathe vapour/aerosol. Provide adequate ventilation.

In case of leakage, eliminate all ignition sources. Use non-sparking tools.

Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up**Other information**

Prevent spread over a wide area (e.g. by containment or oil barriers).

Remove from the water surface (e.g. skimming, sucking).

High slip hazard because of leaking or spilled product.

**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³**

Revision date: 17.03.2023

Product code: 2555-1

Page 4 of 10

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Personal protection equipment: refer to chapter 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not breathe vapour/aerosol. Provide adequate ventilation as well as local exhaustion at critical locations.

Avoid contact with skin and eyes. Take off immediately all contaminated clothing. For industrial purposes only.

Advice on protection against fire and explosion

Flammable liquid and vapour.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Vapours are heavier than air and will spread at floor level. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

Advice on general occupational hygiene

Do not eat, drink, smoke or sneeze at the workplace.

Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes.

Take off contaminated clothing and wash it before reuse.

Protect skin by using skin protective cream.

Wash hands before breaks and after work.

After cleaning apply high-fat content skin care cream.

Do not put any product-impregnated cleaning rags into your trouser pockets.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Further information on handling

Ground and bond container and receiving equipment.

Use non-sparking tools.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store in a place accessible by authorized persons only.

Only use containers specifically approved for the substance/product.

Keep container tightly closed in a cool, well-ventilated place.

Always close containers tightly after the removal of product.

Recommended storage temperature: 5 - 30 °C.

Hints on joint storage

Do not store together with: Oxidising agent,

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Protect against: Heat, Light, Frost, moisture. Protect from direct sunlight.

7.3. Specific end use(s)

Fuels.

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

Air limit values:

Limit value type (country of origin): US-OSHA PEL-Value: 5 mg/m³

MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³

Revision date: 17.03.2023

Product code: 2555-1

Page 5 of 10

Limit value type (country of origin): ACGIH STEL-Value: 10 mg/m³**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses. (EN 166)

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN 420, EN ISO 374.

Suitable material: NBR (Nitrile rubber), FKM (fluoro rubber).

Unsuitable material: Textile material.

Required properties: liquid-tight.

penetration time (maximum wearing period): > 480 min.

Thickness of glove material: 0,4 mm

Before using check leak tightness / impermeability.

Skin protection

Handling larger quantities: Wear suitable protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist generation.

Suitable respiratory protective equipment: A gas filtering equipment (EN 141). AP Combination filter device (DIN EN 141)..

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	light brown
Odour:	characteristic

Test method**Changes in the physical state**

Melting point/freezing point: No data available.

Boiling point or initial boiling point and boiling range: approx. 160 - 400 °C

Flash point: > 55 °C ASTM D 93

Explosive properties

In use may form flammable/explosive vapour-air mixture.

Lower explosion limits: approx. 0,6 vol. %

Upper explosion limits: approx. 6,5 vol. %

Auto-ignition temperature: 220 °C ASTM E 659-78

pH-Value: not applicable

Viscosity / kinematic:
(at 40 °C) approx. 2,0 - 4,5 mm²/s

Partition coefficient n-octanol/water: Log KOW > 3

Vapour pressure:
(at 38 °C) 550 - 650 hPa

MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³

Revision date: 17.03.2023

Product code: 2555-1

Page 6 of 10

Density (at 15 °C): 0,86 g/cm³
 Relative vapour density: > 3

9.2. Other information
Information with regard to physical hazard classes

Oxidizing properties
 No data available.

Other safety characteristics
Further Information

none

SECTION 10: Stability and reactivity
10.1. Reactivity

Flammable liquid and vapour.
 No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

In use may form flammable/explosive vapour-air mixture.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong acid, Strong alkali, Oxidising agent, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.
 In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Harmful if inhaled.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68476-30-2	Fuel oil, No 2, Gasoil - unspecified				
	oral	LD50 > 2000 mg/kg	Rat		OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4100 mg/l	Rat		OECD 403
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Irritant effect on the skin: Causes skin irritation.
 Irritant effect on the eye: slightly irritant but not relevant for classification.

Sensitising effects

Respiratory or skin sensitisation: not sensitising. No known symptoms to date.

**MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³**

Revision date: 17.03.2023

Product code: 2555-1

Page 7 of 10

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Fuel oil, No 2, Gasoil - unspecified)

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Fuel oil, No 2, Gasoil - unspecified)

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria).

12.3. Bioaccumulative potential

Log KOW > 3.

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment cannot be ruled out.

12.4. Mobility in soil

Physical state at 20 °C and 101.3 kPa: liquid.

If product enters soil, it will be mobile and may contaminate groundwater

Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

No information available.

Further information

Discharge into the environment must be avoided.

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

Dispose of waste according to applicable legislation.

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Consult the local waste disposal expert about waste disposal.

List of Wastes Code - residues/unused products

130701 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); wastes of liquid fuels; fuel oil and diesel; hazardous waste

MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³

Revision date: 17.03.2023

Product code: 2555-1

Page 8 of 10

List of Wastes Code - used product

130701 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); wastes of liquid fuels; fuel oil and diesel; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number or ID number: UN 1202
14.2. UN proper shipping name: GAS OIL
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Special Provisions: 640L ADR664
 Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 30
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1202
14.2. UN proper shipping name: GAS OIL
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Special Provisions: 640L
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1202
14.2. UN proper shipping name: GAS OIL
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3

MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³

Revision date: 17.03.2023

Product code: 2555-1

Page 9 of 10



Special Provisions: -
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1202
14.2. UN proper shipping name: GAS OIL
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: GAS OIL

14.6. Special precautions for user

Handling (Transport information): See protective measures under point 7 and 8.

14.7. Maritime transport in bulk according to IMO instruments

MARPOL Anlage I.

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to 2012/18/EU (SEVESO III): 34 Petroleum products and alternative fuels (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams) (-)

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water



according to Regulation (EC) No 1907/2006

MARINE GAS OEL nach DIN ISO 8217, Dichte 0,86 g/cm³

Revision date: 17.03.2023

Product code: 2555-1

Page 10 of 10

Additional information

Restricted to professional users.

The receiver of our product is singularly responsible for adhering to existing laws and regulations. Observe in addition any national regulations!

15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,4,8,9,11,12,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.